



Product Information

Wondermask® Wsol

Water Soluble Mask
2204

Introduction

Wondermask® Wsol is a 100% water soluble mask designed specifically for use in Closed Loop and In-Line aqueous cleaning systems. Wondermask® Wsol dries rapidly, cures within 15 to 30 minutes and is a non-stringing solder mask that dissolves quickly in the water cleaning cycle. Wondermask® Wsol is safe on precious metals, sensitive contacts and is excellent for protecting plated through holes and contact surfaces.

Features / Benefits

- Designed for Closed Loop/In-Line Systems
- 100% Water Soluble
- Lead-Free Compatible
- Safe on Ion Bed & Filters

Chemical Components

Methanol.....	(67-56-1)	45-50%
Non-Ionic Proprietary Material		35-45%
Colloidal Silicon Dioxide.....	(7631-86-9)	5-10%
Surfactants		1-5%
Dye		<1%

Application	Cure Type	Cure Time	Removal	Viscosity	Suggested Thickness	Thinner
Hand	Thermal	30 min @65°C	Soluble in Water 49°C or Higher	11,500-15,500 cps	5-30 mils	Methanol

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Wondermask® WSOL may be ordered in the following container sizes:

2204-8SQ	8 Ounce Squeeze Bottle
2204-G	1 Gallon in Plastic
2204-5G	5 Gallon in Plastic

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe

Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US

Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.
P.O. Box 949
Amarillo, TX 79105
www.techspray.com

2204 8SQ MSDS

[English](#)
[French](#)
[German](#)
[Italian](#)
[Spanish](#)

2204 Bulk MSDS

[English](#)
[French](#)
[German](#)
[Italian](#)
[Spanish](#)

